

SPECIFICATIONS

OUTDOOR

HOUSING

- 11 Gauge steel
- Anchor bolts included
- Handhole standard with grounding provision located inside
- 2" x 4" Handhole standard on 4.0" base
- 3" x 5" Handhole standard on 4.5" and 5.0" bases
- Standard finish is polyester thermosetting powder coat in multiple finishes options



PRS-J-11 Round Non-Tapered Steel Pole

ORDERING INFORMATION

CATALOG #	Height	Finish	Mounting	Base
PRS-J-11	10	BK (Black)	OT (Open Top)	40 (4.0")
	11	BZ (Bronze)	PL (Pole Cap)	45 (4.5")
	12	NA (Natural Aluminum)	20T (2 ^{3/8"} OD Tenon)	50 (5.0")
	13	DN (Dark Natural Aluminum)	30T (2 ^{7/8"} OD Tenon)	
	14	GY (Gray)	35T (3 ^{1/2"} OD Tenon)	
	15	GN (Green)	40T (4" OD x 6" Tenon)	
	16	WH (White)		
	17			
	18			
	19			
	20			
	21			
	22			
	23			
	24			
	25			

Options

EHH	- Extra Handhole
THC	- Threaded Coupling
TNP	- Threaded Nipple
VDI	- Vibration Damper Internal
BCV	- Base Cover
NCV	- Nut Covers
LAB	- Less Anchor Bolts
EPL	- Embedded Pole

EPA Information on 2nd Page

Pole Info.		EPA		
Height	Base	80 MPH (ft. ²)	90 MPH (ft. ²)	100 MPH (ft. ²)
10'	4.00"	31	24	19
	4.50"	40	31	25
	5.00"	51	40	32
11'	4.00"	28	23	19
	4.50"	34	27	21
	5.00"	43	33	27
12'	4.00"	28	23	19
	4.50"	34	27	21
	5.00"	43	33	27
13'	4.00"	23	19	15
	4.50"	28	22	17
	5.00"	36	28	22
14'	4.00"	23	19	15
	4.50"	28	22	17
	5.00"	36	28	22
15'	4.00"	18	14	11
	4.50"	26	20	16
	5.00"	33	26	20
16'	4.00"	16	13	10
	4.50"	24	18	14
	5.00"	31	24	19
17'	4.00"	13	10	8
	4.50"	21	16	12
	5.00"	27	21	16
18'	4.00"	13	10	8
	4.50"	21	16	12
	5.00"	27	21	16
19'	4.00"	11	8	6
	4.50"	15	12	9
	5.00"	20	16	12
20'	4.00"	11	8	6
	4.50"	15	12	9
	5.00"	20	16	12
21'	4.00"	7	5	3
	4.50"	13	10	7
	5.00"	17	13	10
22'	4.00"	7	5	3
	4.50"	13	10	7
	5.00"	17	13	10
23'	4.00"	7	5	3
	4.50"	10	8	6
	5.00"	14	11	8
24'	4.00"	7	5	3
	4.50"	10	8	6
	5.00"	14	11	8
25'	4.00"	7	5	3
	4.50"	10	7	5
	5.00"	13	10	7