

SPECIFICATIONS

OUTDOOR

HOUSING

- Cast aluminum housing

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)

OPTICAL SYSTEM

- Thermal Protection
- 50,000 Hours @ L₇₀
- Power Factor >.90
- 4000K standard
- 3000K and 5000K optional

CODE COMPLIANCE

- cULus Listed for Wet Locations
- Made in USA
- RoHS Compliant

WARRANTY

- 5 Year



PT11-1-G

PT11-2-G

PT11-3-G

PT11-G LED Post Top


ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Lens
PT11-1-G-40L-QT-40K*-FL	40W	4000 Lumens	Frosted
PT11-1-G-60L-QT-40K*-FL	60W	6000 Lumens	Frosted
PT11-2-G-40L-QT-40K*-FL	40W	4000 Lumens	Frosted
PT11-2-G-40L-QT-40K*-CL	40W	4000 Lumens	Clear
PT11-2-G-60L-QT-40K*-FL	60W	6000 Lumens	Frosted
PT11-2-G-60L-QT-40K*-CL	60W	6000 Lumens	Clear
PT11-3-G-40L-QT-40K*-FL	40W	4000 Lumens	Frosted
PT11-3-G-40L-QT-40K*-CL	40W	4000 Lumens	Clear
PT11-3-G-60L-QT-40K*-FL	60W	6000 Lumens	Frosted
PT11-3-G-60L-QT-40K*-CL	60W	6000 Lumens	Clear


*Specify **BL**ack, **WH**ite, **BR**onze

OPTIONS (Factory Installed)

- 30K - 3000K (special order)
- 50K - 5000K (special order)



PT11-1-G



PT11-2-G



PT11-3-G