

SPECIFICATIONS

MULTI FAMILY

HOUSING

- Fade and rust resistant composite construction
- Fits most 3" diameter posts
- Available in black, white, or bronze

ELECTRICAL

- 120VAC
- Operating Temperature: -40°C(-40°F) - 40°C (104°F)

OPTICAL SYSTEM

- Frosted acrylic diffusers
- 50,000 Hours @ L₇₀
- CRI > 80

CODE COMPLIANCE

- cULus Listed for Wet Locations
- RoHS Compliant
- Energy Star Qualified
- Made in USA

WARRANTY

- 5 Year



PT14-G
Post Mount Fixture

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color
PT14-G-13L-120V-30K-*	13W LED	1140 Lumens	3000K
PT14-G-13L-120V-40K-*	13W LED	1280 Lumens	4000K
PT14-G-14L-120V-30K-*	14W LED	1430 Lumens	3000K
PT14-G-14L-120V-40K-*	14W LED	1500 Lumens	4000K

PT14-G-60W-120V-* 60W Medium Base

*Specify Housing: **BL**ack; **WH**ite; **BR**onze

OPTIONS (Factory Installed)

30K	- 3000K A19/E26 LED Lamp (60W model only)
40K	- 4000K A19/E26 LED Lamp (60W model only)

