

SPECIFICATIONS

MULTIFAMILY

HOUSING

- Metal housing in a smooth white finish
- Canless module does not require housing; no housing required for remodel
- Use a new construction plate for new construction
- 26" integral flex whip included

ELECTRICAL

- Quad Tap (QT) 120-277V
- 0-10V Dimming down to 5%
- Operating temperature: -40° - 45° C (-40° - 114° F)
- 2.5Kv Surge Protector
- 4" & 6": Dimmable 0-10V; 8" & 10": 0-10V down to 5%
- THD <20%
- Power factor >.90

ILLUMINATION

- Wattage Selectable
- 5CT (27K/30K/35K/40K/50K)
- Wattage and Color switchable with housing switches
- Frosted polycarbonate lens
- Deep reflector lens reduces glare
- CRI > 90
- Beam angle: 4", 5", 6": 90°; 10":95°
- 70,000 hours @ L₇₀

MOUNTING

- External J-Box and spring mount clips for easy installation

CODE COMPLIANCE

- cETLus Listed for Wet Location
- Energy Star Certified
- CA Title 24
- FCC CFR 47, GCC Part 15

WARRANTY

- 5 Year



RCAN11.5-EN LED Wattage and Color Selectable Downlight

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens	Color Temp
RCAN11.5-EN-4-1L-QT-5CT	4"	5.5W/7W/9W/10W/13W	650/ 850/ 100/ 1200/ 1450 Lms	27K/30K/35K/40K/50K
RCAN11.5-EN-6-1L-QT-5CT	6"	8W/10W/13W/15W/19W	1000/ 1200/ 1500/ 1750/ 2000 Lms	27K/30K/35K/40K/50K
RCAN11.5-EN-6-2L-QT-5CT	6"	9.5W/13W/18.5W/21W/24W	1200/ 1600/ 2200/ 2400/ 2800 Lms	27K/30K/35K/40K/50K
RCAN11.5-EN-8-1L-QT-5CT	8"	16W/20W/23W/27W/30W	2050/ 2450/ 2700/ 3200/ 3350 Lms	27K/30K/35K/40K/50K
RCAN11.5-EN-10-1L-QT-5CT	10"	20W/24W/28W/32W/38W	2250/ 2850/ 3200/ 3600/ 4150 Lms	27K/30K/35K/40K/50K

	Cut-Out Size
4"	Ø4 ^{7/8"}
6"	Ø6 ^{1/8"} ~7 ^{3/16"}
8"	Ø7 ^{1/2"} ~8 ^{7/8"}
10"	Ø9" ~10"

**Dimensions, Options, and
Accessories on 2nd page**

OPTIONS & ACCESSORIES

OPTIONS (Factory Installed)

EM - Emergency Backup

Accessories

EM8W-EN	- External Emergency Battery (8W)
EM15W-EN	- External Emergency Battery (15W)
EM25W-EN	- External Emergency Battery (25W)
RCAN-EN-MTGPHB	- Universal Pre-Mounting Plate with Hanging Bars
RCAN-EN-NCP	- Universal Plate with hanging bars and JBox
RCAN-EN-JBXXL	- Universal Tough in Plate - Extra Long
RCAN-EN-GR4	- 4-8" Goof Ring
RCAN-EN-GR6	- 6.3-10" Goof Ring
RCAN-EN-GR8	- 8-12.5" Goof Ring
RCAN-EN-GR10	- 9-14.1" Goof Ring
RCAN11.5-EN-JBOX	- Junction Box with 4½" Knockouts

Trims

RCAN11.5-EN-*.BLS	- Black Smooth
RCAN11.5-EN-*.CLH	- Clear-Specular Haze Smooth
RCAN11.5-EN-*.CSW	- Clear Specular Haze Inner White Smooth
RCAN11.5-EN-*.WHW	- White Wall Wash**
*Specify Trim Size (4,6,8,10)	
**Only for 4"6", and 8" models	

DIMENSIONS

