

## SPECIFICATIONS

INDOOR

### HOUSING

- Compatible with most 6.25 ceiling cut-outs and 6" mounting frames
- IC Rated - Compatible with insulated, non-insulated, and air tight ceilings
- Aluminum housing with white baffle trim

### ELECTRICAL

- Dimmable to 0-10V
- 120-277Vac
- 50-60Hz
- 18W power consumption
- Operating Temperature: -20°C(-4°F) - 40°C(104°F)

### ILLUMINATION

- Available in 3500K, 4000K, 5000K
- 50,000 Hours @ L<sub>70</sub>
- CRI: 80

### MOUNTING

- Easy to install flex cable into junction box

### CODE COMPLIANCE

- cULus Listed for Wet Locations
- Energy Star Qualified
- RoHS Compliant

### WARRANTY

- 5 Year warranty



## RCAN6-AT2 6" LED Architectural Recessed Can

## ORDERING INFORMATION

CATALOG#	Lumens	Color
RCAN6-AT2-BAF-35K	1700	3500K
RCAN6-AT2-BAF-40K	1700	4000K
RCAN6-AT2-BAF-50K	1700	5000K

### ACCESSORIES (Order Separately)

RCAN6-AT-TRM-SQ	- Snap on Square Trim
RCAN6-AT-TRM-SWH	- Silver/White (snap on trim)
RCAN6-AT-TRM-BL	- Black (snap on trim)
RCAN6-AT-TRM-BZ	- Bronze (snap on trim)
RCAN6-AT-TRM-NI	- Nickel (snap on trim)
RCAN6-AT-MFJB	- Mounting Frame with JBox

