

SPECIFICATIONS

INDOOR

HOUSING

- Die-formed, cold rolled steel
- Available in 1x4, 2x2, and 2x4 housings
- Post powder paint in matte white finish

ELECTRICAL

- 0-10V Dimmable driver standard

OPTICAL SYSTEM

- Translucent opal white acrylic overlay diffuser
- CCT: 30K-50K available
- CRI \geq 82

MOUNTING

- Perforated basket flexes over mounting studs on housing for easy installation
- Wiring access plate or knockouts provided for flex conduit attachment
- Hole provided for chain mounting support
- Surface mount options available

CODE COMPLIANCE

- cETLus Listed for Damp Locations (up to 67W)
- BAA Compliant

WARRANTY

- 5 Year



RCBIID LED Direct/Indirect Basket

ORDERING INFO

Housing	Wattage/Lumens	Driver	Color
RCBIID-22 (2x2)	2x2	QT (120-277V, 0-10V Dimming)	30K
RCBIID-24 (2x4)	24L (24W, 2160 Lm)	SD (120-277V, Step Dimming)	35K
	28L (28W, 2160 Lm)	347V (347V, 0-10V Dimming)	40K
	35L (35W, 2720 Lm)	120V (120V, Triac Dimming)	50K
	2x4	277V (277V, Triac Dimming)	
	32L (32W, 2760 Lm)		
	48L (48W, 3840 Lm)		
	57L (57W, 4320 Lm)		
	72L (72W, 5600 Lm)		

OPTIONS (Ships Installed)

EBLED5W	- 5W Emergency Battery, 1700 Lumens
EBLED10W	- 10W Emergency Battery, 850 Lumens
WP6	- 6' 3-Wire Flex Conduit