

SPECIFICATIONS

INDOOR

HOUSING

- Housing is die-formed steel
- Baked white enamel finish
- Corrosion and scratch resistant
- Flush door with clam latches that hinges from either side
- Equipped with earthquake clips
- Easy access plate for quick wiring
- Available in 2x2 and 2x4 size housings

CODE COMPLIANCE

- cULus Listed for Damp Locations
- FCC Compliant
- RoHS Compliant
- BAA Compliant

WARRANTY

- 5 Year

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimming standard
- 4kV Surge Protection
- 50,000 hours @ L₇₀

OPTICAL SYSTEM

- Built to order wattage/lumen options; contact factory
- .100 Acrylic prismatic lens standard (multiple lenses available)
- CRI >80
- Pf >.90
- THD <20%
- Offered in 30K, 35K, 40K, 50K

ORDERING INFORMATION

CATALOG#	Size	Wattage	Lumens
RT4-K-22X17L-QT-*	2X2	17W	3,166 Lumens
RT4-K-22X24L-QT-*	2X2	24W	4,350 Lumens
RT4-K-22X31L-QT-*	2X2	31W	5,470 Lumens
RT4-K-22X39L-QT-*	2X2	39W	6,452 Lumens
RT4-K-22X48L-QT-*	2X2	48W	8,640 Lumens
RT4-K-22X124L-QT-*	2X2	124W	21,112 Lumens

RT4-K-24X17L-QT-*	2X4	17W	3,220 Lumens
RT4-K-24X24L-QT-*	2X4	24W	4,480 Lumens
RT4-K-24X30L-QT-*	2X4	30W	5,705 Lumens
RT4-K-24X37L-QT-*	2X4	37W	6,910 Lumens
RT4-K-24X48L-QT-*	2X4	48W	8,640 Lumens
RT4-K-24X70L-QT-*	2X4	70W	11,797 Lumens
RT4-K-24X114L-QT-*	2X4	114W	19,446 Lumens
RT4-K-24X171L-QT-*	2X4	171W	31,911 Lumens
RT4-K-24X240L-QT-*	2X4	240W	36,460 Lumens

*Specify Color; 30K, 35K, 40K, 50K

OPTIONS (Factory Installed)

EM5	- 5W Emergency Battery
EM10	- 10W Emergency Battery
EM14	- 14W Emergency Battery
OCSD	- Bi-Level Dimming System
CP	- Cord and Plug
AL125	- .125 Prismatic Lens
FL	- Frosted Lens (over LED board)
PC	- Polycarbonate Lens
G3	- Triple Gasket

ACCESSORIES (Order Separately, Ships on Side)

RT4-K-WG - Wireguard



RT4-K Customizable Recessed Troffer

