

SPECIFICATIONS

INDOOR

HOUSING

- Gasketed housing and door frame
- 18 or 20 gauge cold roll steel
- Offered in 1X4, 2X2, and 2X4 sizes

ELECTRICAL

- Quad Tap (QT) - 120-277V or 347-480V
- Pf>.90
- 0-10V Dimmable driver standard
- Operating Temperature: -30°C - 50°C (-22°F - 122°F)
- 100,000 hours @ L₇₀

OPTICAL SYSTEM

- Multiple lenses available
- CRI >80
- Offered in 2700K, 3000K, 3500K, 4000K, and 5000K

MOUNTING

- Recessed grid mounting

CODE COMPLIANCE

- ETL Listed for Wet Locations
- CSA Listed
- Made in the USA
- BAA Compliant
- BABA Compliant
- NSF Rated
- IP65 Rated

WARRANTY

- 5 Year



RT8-AEL NSF Rated LED Troffer

ORDERING INFORMATION

MODEL#	Size x Wattage	Driver	Color
RT8-AEL	1X4ft.	QT	27K
	14X12L (12W, 2000 Lm)	480V	30K
	14X25L (25W, 5000 Lm)		35K
			40K
			50K
	2X2 ft.		
	22X12L (12W, 2000 Lm)		
	22X25L (25W, 5000 Lm)		
	22X44L (44W, 7000 Lm)		
	22X56L (56W, 9000 Lm)		
	2X4 ft.		
	24X12L (12W, 2000 Lm)		
	24X25L (25W, 5000 Lm)		
	24X44L (44W, 7000 Lm)		
	24X56L (56W, 9000 Lm)		
	24X69L (69W, 11,000 Lm)		
	24X81L (81W, 13,000 Lm)		
	24X94L (94W, 15,000 Lm)		
	24X112L (112W, 18,000 Lm)		
	24X125L (125W, 20,000 Lm)		

OPTIONS (Factory Installed)

20G	- 20 Gauge Cold Roll Steel Housing (0.63" Aluminum Housing Standard)
18G	- 18 Gauge Cold Roll Steel Inset Door Frame (0.63" Aluminum Housing Standard)
EM14	- 14W Emergency Battery
CP125	- .125 Clear Polycarbonate
CP250	- .250 Clear Polycarbonate
PA156	- .156 Prismatic Acrylic (inverted)
PA125	- .125 Prismatic Acrylic (inverted)
PA187	- .187 Prismatic Acrylic (inverted)
90C	- 90 CRI
WHAM	- Anti-Microbial White Paint
OCS	- Occupancy Sensor

Dimensions on 2nd page

DIMENSIONS

