

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Die cast aluminum housing
- Offered in 11" and 14" housings
- White powdercoat finish standard

ELECTRICAL

- 120V
- Dimmable driver standard
- Operating Temperature: -40°C - 40°C (-40°F - 104°F)

OPTICAL SYSTEM

- White acrylic diffuser
- 50,000 hours @ L₇₀
- CRI: 80
- 3000K and 4000K available

MOUNTING

- Ceiling Mount

CODE COMPLIANCE

- cULus Listed for Damp Locations
- RoHS Compliant
- Energy Star Compliant

WARRANTY

- 5 Year



SD12-G LED Dome

ORDERING INFORMATION

| MODEL # | Wattage/Voltage/Color (description) |
|-----------|--|
| SD12-G-11 | 12L-120V-30K (12W, 1020 Lumens, 3000K, 120V, 90CRI) |
| SD12-G-14 | 12L-120V-40K (12W, 1040 Lumens, 4000K, 120V, 90CRI) |
| | 13L-120V-30K (13W, 1140 Lumens, 3000K, 120V, 80CRI) |
| | 13L-120V-40K (13W, 1280 Lumens, 4000K, 120V, 80CRI) |
| | 14L-120V-30K (14W, 1430 Lumens, 3000K, 120V, 80CRI) |
| | 14L-120V-40K (14W, 1500 Lumens, 4000K, 120V, 80CRI) |
| | 16L-120V-30K (16W, 1370 Lumens, 3000K, 120V, 90CRI) |
| | 16L-120V-40K (16W, 1400 Lumens, 4000K, 120V, 90CRI) |
| | 17L-QT-30K (17W, 1278 Lumens, 3000K, 120-277V, 80CRI, 11" only) |
| | 22L-120V-30K (22W, 1950 Lumens, 3000K, 120V, 80CRI) |
| | 22L-120V-40K (22W, 2130 Lumens, 4000K, 120V, 80CRI) |
| | 22L-QT-30K (22W, 1704 Lumens, 3000K, 120-277V, 80CRI, 14" only) |
| | 22L-QT-40K (22W, 1824 Lumens, 4000K, 120-277V, 80CRI, 14" only) |
| | 24L-120V-30K (24W, 1980 Lumens, 3000K, 120V, 90CRI) |
| | 24L-120V-40K (24W, 2020 Lumens, 4000K, 120V, 90CRI) |
| | 1X40W-120V (40W Max Incandescent, Medium Base, 120V, 11" only) |
| | 2X40W-120V (2x40W Max Incandescent, Medium Base, 120V, 11" only) |

OPTIONS (Factory Installed)

- | | |
|-----|--|
| OCS | - Motion Sensor (not available on incandescent models) |
| 30K | - 3000K A19/E26 LED Lamp (incandescent models only) |
| 40K | - 4000K A19/E26 LED Lamp (incandescent models only) |

