

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Steel housing
- Finishes offered in white or brushed nickel
- Round or square
- 11", 13", or 15" models available

ELECTRICAL

- 120V
- Dimmable TRIAC
- ELV, 10-100%

OPTICAL SYSTEM

- Frosted acrylic lens
- Beam angle: 120°
- 3000K or 4000K
- 90 CRI
- 50,000 hours @L₇₀

CODE COMPLIANCE

- cETLus Listed for Damp Locations
- Title24 JA8 Compliant
- Energy Star Listed

WARRANTY

- 5 Year



SD38 LED Slim Flush Mount

ORDERING INFORMATION

CATALOG#	Shape	Wattage	Lumens	Color	Size
SD38-R-15L-120V-30K-*	Round	15W	1000 lms	3000K	11" W x 1" D
SD38-S-15L-120V-30K-*	Square	15W	988 lms	3000K	11" W x 11" L x 1 1/4" D
SD38-R-15L-120V-40K-*	Round	15W	1000 lms	4000K	11" W x 1" D
SD38-S-15L-120V-40K-*	Square	15W	988 lms	4000K	11" W x 11" L x 1 1/4" D
SD38-R-20L-120V-30K-*	Round	20W	1450 lms	3000K	13" W x 1" D
SD38-S-20L-120V-30K-*	Square	20W	1199 lms	3000K	13" W x 13" L x 1 1/4" D
SD38-R-20L-120V-40K-*	Round	20W	1450 lms	4000K	13" W x 1" D
SD38-S-20L-120V-40K-*	Square	20W	1199 lms	4000K	13" W x 13" L x 1 1/4" D
SD38-R-30L-120V-30K-*	Round	30W	1900 lms	3000K	15" W x 1" D
SD38-S-30L-120V-30K-*	Square	30W	1776 lms	3000K	15" W x 15" L x 1 1/4" D
SD38-R-30L-120V-40K-*	Round	30W	1900 lms	4000K	15" W x 1" D
SD38-S-30L-120V-40K-*	Square	30W	1776 lms	4000K	15" W x 15" L x 1 1/4" D

*Specify Finish: **WH**-White **BN**-Brushed Nickel(Only available in 30K)

