

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Die-cast aluminum housing
- Available in white, black, or brushed nickel finish
- Available in 5", 7", 9", or 11"

OPTICAL SYSTEM

- CRI: 90
- 3000K
- 5CT: Selectable (27K/30K/35K/40K/50K)
- Beam angle: 100°
- 50,000 hours @L₇₀

ELECTRICAL

- 120V
- Power Factor > .9
- Triac and ELV Dimmable down to 5%
- Operating Temperature: -17°C (0°F) - 45°C (113°F)

MOUNTING

- Compatible with 3O or 4O J-Box

CODE COMPLIANCE

- cETLus Listed for Indoor Locations
- Energy Star Rated
- Title24 JA8 Compliant
- FFC CFR 47

WARRANTY

- 5 Year



SD39-EN LED Canopy

ORDERING INFORMATION

CATALOG#	Size	Wattage	Lumens	Driver	CCT	Housing
SD39-EN-12L-120V-30K-*	5"	12W	850 Lms	120V	3000K	Specify
SD39-EN-12L-120V-5CT-WH	5"	12W	850 Lms	120V	27K/30K/35K/40K/50K	White
SD39-EN-15L-120V-30K-*	7"	15W	1100 Lms	120V	3000K	Specify
SD39-EN-15L-120V-5CT-WH	7"	15W	1100 Lms	120V	27K/30K/35K/40K/50K	White
SD39-EN-18L-120V-30K-*	9"	18W	1300 Lms	120V	3000K	Specify
SD39-EN-18L-120V-5CT-WH	9"	18W	1300 Lms	120V	27K/30K/35K/40K/50K	White
SD39-EN-20L-120V-30K-*	11"	20W	1500 Lms	120V	3000K	Specify
SD39-EN-20L-120V-5CT-WH	11"	20W	1500 Lms	120V	27K/30K/35K/40K/50K	White

*Specify Finish: **WH-White**, **BK-Black**, **BN-Brushed Nickel**

OPTIONS (Factory Installed)

- EM - Emergency Backup

DIMENSIONS

