

## SPECIFICATIONS

## MULTI-FAMILY

### HOUSING

- Can be used in new construction and remodel applications
- Metal housing
- Available in 4", 6" and 8" housing

### ELECTRICAL

- 120V
- Operating Temperature -20°C - 40°C (-4°F - 104°F)
- Power Factor >.9
- Triac dimmable down to 5%

### OPTICAL SYSTEM

- Frosted acrylic lens
- MCT (selectable between 30K/40K/50K)
- CRI > 90
- 50,000 hours @ L<sub>70</sub>

### MOUNTING

- Mounts to a 3" or 4" JBox
- Recessed can coverter optional (4" & 6" only)

### CODE COMPLIANCE

- cETLus Listed for Wet Locations
- Meets UL Requirements
- Energy Star Rated
- Title24 Compliant
- FCC Compliant

### WARRANTY

- 5 Year



**SD5  
LED Disk**

## ORDERING INFORMATION

| MODEL#                                                           | Description                                      |
|------------------------------------------------------------------|--------------------------------------------------|
| SD5-4-10L-120V-5CT-*                                             | 4", 10W, 650 Lumens, 27/30/35/40/50K             |
| SD5-4-10L-120V-MCT-BN                                            | 4", 10W, 650 Lumens, 30K/40K/50K, Brushed Nickel |
| SD5-6-15L-120V-30K                                               | 6", 15W, 1000 Lumens, 3000K, White               |
| SD5-6-15L-120V-40K                                               | 6", 15W, 1000 Lumens, 4000K, White               |
| SD5-6-15L-120V-5CT-#                                             | 6", 15W, 1000 Lumens, 27/30/35/40/50K            |
| SD5-8-27L-120V-5CT-WH                                            | 8", 27W, 2100 Lumens, 27/30/35/40/50K, White     |
| <i>*Specify WH-White, BZ-Bronze</i>                              |                                                  |
| <i>#Specify WH-White, BZ-Bronze, BN-Brushed Nickel, BK-Black</i> |                                                  |

### ACCESSORIES (Ships on Side)

- EM25-EN - 25W Remote Emergency Battery
- SD5-CAN4 - 4" Recessed Can Converter
- SD5-CAN6 - 6" Recessed Can Converter

