

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Can be used in new construction and remodel applications
- Metal housing and trim
- Offered in 4" and 6" housings
- White trim provided standard; black, bronze, and brushed nickel optional
- Spring clips with remote JBox eliminates the need for can

OPTICAL SYSTEM

- Frosted acrylic lens
- 110° Beam angle
- CRI > 90
- 5CT selectable 27K/30K/35K/40K/50K
- 50,000 Hours @ L₇₀

ELECTRICAL

- 120V standard
- Triac dimmable down to 5%
- 2.5Kv Surge protector
- 2 hour fire rating

MOUNTING

- External remote junction box mounts inside ceiling (IC rated)
- Trim snaps into place with tension spring clips

CODE COMPLIANCE

- cETLus Listed for Wet Locations
- Meets UL263 Requirements
- Energy Star Rated
- JA8 Title24 Compliant
- Fire Rated
- FCC Compliant

WARRANTY

- 5 Year



SD9-FR
Snap-In Fire-Rated
LED Downlight

ORDERING INFORMATION

CATALOG#	Size	Wattage	Lumens	CCT
SD9-FR-4-12L-120V-5CT	4"	12W	840 Lumens	27K/30K/35K/40K/50K
SD9-FR-6-15L-120V-5CT	6"	15W	1150 Lumens	27K/30K/35K/40K/50K

Options (Ships Installed)

- EM - Emergency Battery Backup

Accessories (Order Separately, Ships on Side)

- SD9-R-4-BRZ - 4" Bronze Trim (White standard)
- SD9-R-4-BRN - 4" Brushed Nickel Trim (White standard)
- SD9-R-4-BLK - 4" Black Trim (White standard)
- SD9-R-6-BRZ - 6" Bronze Trim (White standard)
- SD9-R-6-BRN - 6" Brushed Nickel Trim (White standard)
- SD9-R-6-BLK - 6" Black Trim (White standard)
- RCAN-EN-MTGP - Universal Mounting Plate with Hanging Bars
- RCAN-EN-JBOX6 - 6' JBox Connector Extension Cable
- RCAN-EN-JBOX10 - 10' JBox Connector Extension Cable
- RCAN-EN-JBOX12 - 12' JBox Connector Extension Cable
- SD9-4-RI - 4" Rough-In Plate (6^{1/2"} x 13^{1/4"})
- SD9-6-RI - 6" Rough-In Plate (8^{1/2"} x 17^{1/4"})
- SD9-UNV-RI - Universal Rough-In Plate, Extra Long

