

SPECIFICATIONS

MULTIFAMILY

HOUSING

- Cold rolled steel housing

ELECTRONIC

- 120V
- Quad-Tap (120-277V)
- Dimmable Driver on 38W model

ILLUMINATION

- Opal Acrylic Shade

CODE COMPLIANCE

- cULus Listed for Damp Location
- JA8/CEC Title24 Compliant (38W model)

WARRANTY

- 5 Year Warranty



SDR3 LED Round Ceiling Light

Ordering Information

CATALOG#	Wattage	Lumens	Color	Voltage	Dimensions (ODxH)
SDR3-9L-120V-30K-*	9W	1000	3000K	120V	11.0" x 4.3"
SDR3-17L-120V-40K-*	17W	1600	4000K	120V	11.0" x 4.3"
SDR3-24L-QT-30K-*	24W	2560	3000K	120V-277V	14.0" x 4.6"
SDR3-35L-QT-40K-*	35W	3280	4000K	120V-277V	18.9" x 4.6"
SDR3-28L-QT-30K-*	38W	3280	3000K	120V-277V	18.9" x 4.6"
SDR3-23W-120V-27K-*	1x32W GU24	2700K	120V	11.0" x 4.3"	
SDR3-23W-120V-40K-*	1x32W GU24	4000K	120V	11.0" x 4.3"	
SDR3-26W-120V-27K-*	2x13W GU24	2700K	120V	14.0" x 4.6"	
SDR3-26W-120V-40K-*	2x13W GU24	4000K	120V	14.0" x 4.6"	

*Specify **SN-Satin Nickel**; **ORB-Oil Rubbed Bronze**

Options

35K	-	3500K (extended lead time) -LED
50K	-	5000K (extended lead time) -LED

