

SPECIFICATIONS

OUTDOOR

HOUSING

- Die cast aluminum housing
- Available in black, white, silver, and bronze finishes
- 16AWG Cable (118")

ELECTRICAL

- Quad Tap (120-277V)
- 277-480V optional
- 12V auxiliary dimming standard
- Operating Temp: -40°F - 175°F (-40°C - 80°C)
- Power Factor > 0.95
- 75,000 Hours @ L₇₀
- 10kV Surge protection standard

OPTICAL SYSTEM

- 4000K and 5000K available
- CRI: 80
- Nema III, Nema IV, and Nema V distributions available

MOUNTING

- Trunnion Mount standard
- Slipfitter optional

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Premium Listed
- ROHS Compliant
- FCC Compliant

WARRANTY

- 5 Year



SL6-WS LED SportsLight

ORDERING INFORMATION

CATALOG#	Illumination	Voltage	CCT	Distribution	Color
SL6-WS	400L (400W, 56,800 Lm)	QT (120-277V)	40K	T3	BZ
	600L (600W, 85,200 Lm)	480V (277V - 480V)	50K	T4	WH
				T5	BK
					SV

OPTIONS (Factory Installed)

SF - SlipFitter (Trunnion standard)

ACCESSORIES (Factory Installed)

SL6-WS-REM - Dali-2 Dimmable Controller

