

## SPECIFICATIONS

MULTI FAMILY

### HOUSING

- Die formed cold rolled steel
- Available in Satin Nickel standard; Oil Rubbed Bronze optional

### ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V

### OPTICAL SYSTEM

- High performance acrylic shade
- CRI > 80
- 3000K - 5000K available
- MCT option (Adjustable Color Temperature - 30K, 35K, 40K)

### CODE COMPLIANCE

- cETLus Listed for Damp Locations
- Meets UL Requirements
- Energy Star Listed
- JA8, T24 Compliant (24W)

### WARRANTY

- 5 Year



## SR1 LED Spill Ring

## ORDERING INFORMATION

CATALOG#	Wattage	Lumens	Color	Dimensions (LxWxH)	Designation
SR1-23L-QT-30K	23W	2,200 Lumens	3000K	24.5" x 5.7" x 4.5"	
SR1-23L-QT-MCT	23W	2,200 Lumens	Adjustable	24.5" x 5.7" x 4.5"	
SR1-24L-QT-30K	24W	1,980 Lumens	3000K	24.5" x 5.7" x 4.5"	90CRI, JA8 T24
SR1-36L-QT-30K	36W	3,260 Lumens	3000K	36.5" x 5.7" x 4.5"	
SR1-36L-QT-MCT	36W	3,260 Lumens	Adjustable	36.5" x 5.7" x 4.5"	
SR1-46L-QT-30K	46W	4,600 Lumens	3000K	48.5" x 5.7" x 4.5"	
SR1-46L-QT-MCT	46W	4,600 Lumens	Adjustable	48.5" x 5.7" x 4.5"	

### Options (Factory Installed)

ORB	- Oil Robbed Bronze (satin nickel standard)
35K	- 3500K (replaces 30K in part number)
40K	- 4000K (replaces 30K in part number)
50K	- 5000K (replaces 30K in part number)

