

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Die-formed cold-rolled steel
- Finishes available in satin nickel and oil rubbed bronze

ELECTRICAL

- QT (120-277V)

OPTICAL SYSTEM

- Acrylic Lens
- CCT Available in 3000K, 4000K or MCT (30/35/40K)
- 90 CRI

CODE COMPLIANCE

- cETLus Listed for Indoor Locations
- EnergyStar Listed

WARRANTY

- 5 Year



SR8 LED Spill Ring

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	CCT	Dimensions
SR8-28L-QT-MCT-*	28W	2720 Lm	30/35/40K	32.3" x 18.1" x 4.3"
SR8-35L-QT-30K-*	35W	3485 Lm	3000K	28.3" x 14.1" x 4.4"
SR8-35L-QT-40K-*	35W	3660 Lm	4000K	28.3" x 14.1" x 4.4"
SR8-46L-QT-30K-*	46W	4470 Lm	3000K	32.3" x 18.1" x 4.3"
SR8-46L-QT-40K-*	46W	4700 Lm	4000K	32.3" x 18.1" x 4.3"
SR8-46L-QT-MCT-*	46W	4470 Lm	30/35/40K	32.3" x 18.1" x 4.3"

*Specify Housing: **SN**-Satin Nickel, **ORB**-Oil Rubbed Bronze

