

## SPECIFICATIONS

INDOOR

### HOUSING

- Available in 4" and 6" housing
- Die-cast aluminum housing and trim
- White finish standard (black and bronze trims available)

### ELECTRICAL

- 120V (120V-277V housing and cans available)
- Operating temperature: -40° C (-40°F) - 45° (114° F)
- Down to 5% dimmable with compatible dimmers
- Built-in 2.5Kv surge protector

### ILLUMINATION

- Frosted acrylic lens
- 50,000 hours @L<sub>70</sub>
- CRI > 90
- Beam angle: 100°
- Color selectable (2700K, 3000K, 3500K, 4000K, 5000K)

### MOUNTING

- 4" tension clip springs fit into most 4" compatible recessed cans
- 6" spring clips fit into most 5" & 6" compatible recessed cans
- Retro fit into existing housing with E26 socket

### CODE COMPLIANCE

- cETLus Listed for wet locations
- Energy Star rated
- Title24 compliant
- FCC compliant

### WARRANTY

- 5 Year warranty

Recommended Dimmers	
Manufacturer	Model #
Lutron	DVCL-153P
Lutron	MACL-153MH
Lutron	CTCL-153P
Lutron	P-PKG1W-WH-R
Leviton	R62-06674-P0W
Leviton	R12-06672-1LW
Leviton	6602
Leviton	R50-IPL06-10M
Eaton	SAL06P-LA-K

## ORDERING INFORMATION

CATALOG#	Wattage	Lumens	Voltage	Color	Size
SRCAN1-EN-11L-120V-5CCT	11W	750 Lm	120V	5CT	4"
SRCAN1-EN-14L-120V-5CCT	14W	1100 Lm	120V	5CT	6"

### ACCESSORIES (Order Separately, Ships on Side)

EM25-EN	- Emergency Battery
SRCAN1-EN-4-BK	- 4" Smooth Black Trim
SRCAN1-EN-4-BZ	- 4" Smooth Bronze Trim
SRCAN1-EN-6-BK	- 6" Smooth Black Trim
SRCAN1-EN-6-BZ	- 6" Smooth Bronze Trim
SRCAN1-EN-C4N	- 4" IC Rated Can (New Construction)
SRCAN1-EN-C4R	- 4" IC Rated Can (Remodel)
SRCAN1-EN-C6N	- 6" IC Rated Can (New Construction)
SRCAN1-EN-C4R	- 6" IC Rated Can (Remodel)
SRCAN1-EN-4FR	- 4" Fire Rated IC Can (New Construction)
SRCAN1-EN-6FR	- 6" Fire Rated IC Can (New Construction)



## SRCAN1-EN 4/6" Square CCT Selectable Downlight

