

SPECIFICATIONS

INDOOR

HOUSING

- Offered in 4' or 8' lengths
- Aluminum housing
- Powder-coat white finish
- Linkable

ELECTRICAL

- Quad Tap (QT) 120-277V
- -4°F - 122°F (-20°C - 50°C)
- Pf > .90
- Type II Light Distribution
- 50,000 hours @ L₇₀

OPTICAL SYSTEM

- PC Frosted square lens
- 0-10V Dimming
- Beam angle: 130°
- CRI > 80
- MCT: Selectable between 3500K/4100K/5000K

CODE COMPLIANCE

- cUL Listed
- DLC Listed
- Title24 Compliant
- IP40

WARRANTY

- 5 Year



ST11-K LED Strip Light

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	CCT
ST11-K-4X1L-QT-MCT	34W/38W/45W	4420/ 4940/ 5850 Lms	35K/41K/50K
ST11-K-8X1L-QT-MCT	65W/75W/90W	8645/ 9975/ 11,970 Lms	35K/41K/50K

OPTIONS (Factory Installed)

OCS	- Occupancy Sensor
MOCS	- Microwave Motion & Daylight Sensor
EM	- 8W Emergency Battery Backup

ACCESSORIES (order separately, ships on side)

ST11-QCB	- Swivel Quick Connect Adjustable Elbow
ST11-JB	- Row Aligner
ST11-VHOOK	- V-Hooks (2 per set)
CK5-K	- 60" Chain Kit

Dimensions listed on 2nd page

DIMENSIONS

