

SPECIFICATIONS

INDOOR

HOUSING

- Heavy gauge steel housing
- Baked white enamel
- Socket bar, end plate, and ballast cover snap on for tool-free assembly
- End-plate doubles as coupler when fixture is used in continuous run
- Knockouts for pendant/surface mount. Linkable with 7/8" knockout on end plate

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable driver standard
- Power factor > .90
- THD < 20%
- 4kV Surge Protection
- 50,000 hours @ L₇₀

OPTICAL SYSTEM

- White, silver, and asymmetrical reflectors available
- CRI > 80
- Offered in 30 - 50K

CODE COMPLIANCE

- cULus Listed for Damp Locations
- BAA Compliant
- FCC Compliant
- RoHS Compliant

WARRANTY

- 5 Year



ST15-K LED Channel Strip Light

ORDERING INFORMATION

MODEL #	Size x Wattage	Voltage	CCT
ST15-K	2FT	QT (120-277V)	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		
	4FT		
	4X17L (17W, 3220 Lm)		
	4X24L (24W, 4480 Lm)		
	4X30L (30W, 5705 Lm)		
	4X37L (37W, 6910 Lm)		
	4X48L (48W, 8640 Lm)		
	4X70L (70W, 11,797 Lm)		
	8FT		
	8X17L (17W, 3220 Lm)		
	8X24L (24W, 4480 Lm)		
	8X30L (30W, 5705 Lm)		
	8X37L (37W, 6910 Lm)		
	8X48L (48W, 8640 Lm)		
	8X70L (70W, 11,797 Lm)		

OPTIONS (Factory Installed)

EM5	- 5W Emergency Battery
EM10	- 10W Emergency Battery
EM14	- 14W Emergency Battery
OCS	- External Occupancy Sensor
OCSD	- Bi-Level Dimming System
WH	- White Reflector
SV	- Silver Reflector
AS	- Asymmetrical Reflector
GO	- Grounded Outlet
TS	- Toggle Switch
RS	- Rocker Switch
PC	- Pull Chain Switch
CP	- Cord & Plug

ACCESSORIES (Order Separately)

ST1-K-WG4 - 4' Wireguard

