

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum sheet housing
- Corrosion, discoloration, and scratch resistant
- Semi-gloss coating
- White finish
- Offered in 4', and 8' size housings
- Suitable for mounting less than 25'
- Surface mount, 10' hanging cables available

ELECTRICAL

- Quad Tap (QT) 120-277
- 50/60 Hz
- -4°F - 104°F (-20°C - 40°C)
- 0-10V Dimmable driver standard
- 50,000 hours @ L₇₀
- Power Factor > 0.9
- THD < 10%

OPTICAL SYSTEM

- Anti-UV Frosted Polycarbonate Lens
- MCT: Selectable between: 35K/40K/50K
- Frosted polycarbonate lens
- CRI > 80

CODE COMPLIANCE

- cULus Listed for Damp Locations
- DLC Premium Listed
- RoHS Compliant
- FCC Compliant

WARRANTY

- 5 Year



ST17-S-MCT Selectable LED Strip

ORDERING INFORMATION

Model#	Size	Wattage	Lumens	Color Temp
ST17-S-4X1L-QT-MCT	4'	24W / 32W / 40W	3120 / 4160 / 5200 Lms	35K/40K/50K
ST17-S-8X1L-QT-MCT	8'	60W / 70W / 80W	8100 / 9450 / 10,800 Lms	35K/40K/50K

OPTIONS (Factory Installed)

EM8	- 8W Emergency Battery
EM20	- 20W Emergency Battery
OSCD	- Bi-Level Dimming System

ACCESSORIES (Order Separately)

ST17-S-WG4	- 4' Wireguard
ST17-S-WG8	- 8' Wireguard
GK10-S	- 10' Hanging Aircraft Cables

