

SPECIFICATIONS

INDOOR

HOUSING

- Heavy Gauge Steel housing
- Baked white enamel finish
- Available in 2' and 4' models

ELECTRICAL

- 120-277VAC
- 0-10V Dimmable Driver Standard

OPTICAL SYSTEM

- Extruded White Acrylic Lens
- 3000K - 5000K

MOUNTING

- Wiring knockouts on back of housing

CODE COMPLIANCE

- cULus Listed for Damp Locations

WARRANTY

- 5 Year



SW4-K LED Stairwell

ORDERING INFORMATION

CATALOG #	Length	Wattage	Lumens
SW4-K-2X17L-QT-*	2'	17W	3166 Lumens
SW4-K-2X24L-QT-*	2'	24W	4350 Lumens
SW4-K-2X31L-QT-*	2'	31W	5470 Lumens
SW4-K-2X39L-QT-*	2'	39W	6452 Lumens
SW4-K-4X20L-QT-*	4'	20W	3158 Lumens
SW4-K-4X30L-QT-*	4'	30W	4480 Lumens
SW4-K-4X40L-QT-*	4'	40W	5684 Lumens
SW4-K-4X42L-QT-*	4'	42W	6318 Lumens
SW4-K-4X60L-QT-*	4'	60W	8960 Lumens
SW4-K-4X84L-QT-*	4'	84W	11368 Lumens

*Specify **30K**, **35K**, **40K**, **50K**

OPTIONS (Factory Installed)

EBLED	- Emergency Ballast
OCS	- Internal Occupancy Sensor
XOCS	- External Occupancy Sensor
BLD	- Bi-Level Dimming
GO	- Grounded Outlet
TOG	- Toggle Switch
PCK	- Pull Chain Switch
NL	- Night Light