

SPECIFICATIONS

INDOOR

HOUSING

- Heavy Gauge Steel housing
- Baked white enamel finish
- Available in 2' and 4' models

ELECTRICAL

- 120-277VAC
- 0-10V Dimmable Driver Standard
- Pf > .90
- THD < 20%
- 4kV Surge Protection
- 50,000 hours @ L₇₀

OPTICAL SYSTEM

- Extruded White Acrylic Lens
- CRI > 80
- 3000K - 5000K

MOUNTING

- 7/8" Wiring knockouts on back of housing

CODE COMPLIANCE

- cULus Listed for Damp Locations
- FCC Compliant
- RoHS Compliant
- BAA Compliant

WARRANTY

- 5 Year



SW4-K LED Stairwell

ORDERING INFORMATION

CATALOG #	Length	Wattage	Lumens
SW4-K-2X17L-QT-*	2'	17W	3166 Lumens
SW4-K-2X24L-QT-*	2'	24W	4350 Lumens
SW4-K-2X31L-QT-*	2'	31W	5470 Lumens
SW4-K-2X39L-QT-*	2'	39W	6452 Lumens
SW4-K-4X17L-QT-*	4'	17W	3220 Lumens
SW4-K-4X24L-QT-*	4'	24W	4480 Lumens
SW4-K-4X30L-QT-*	4'	30W	5705 Lumens
SW4-K-4X37L-QT-*	4'	37W	6910 Lumens
SW4-K-4X48L-QT-*	4'	48W	8640 Lumens
SW4-K-4X70L-QT-*	4'	70W	11797 Lumens

*Specify 30K, 35K, 40K, 50K

OPTIONS (Factory Installed)

EM5	- 5W Emergency Battery
EM10	- 10W Emergency Battery
EM14	- 14W Emergency Battery
OCSD	- Bi-Level Dimming System
GO	- Grounded Outlet
TS	- Toggle Switch
PC	- Pull Chain Switch
NL	- Night Light