

SPECIFICATIONS

INDOOR

FEATURES

- Single or Double-Ended Wiring
- Replacement for Fluorescent Lamps

ELECTRICAL

- 120-277V 60Hz
- Operating Temperature: -20°C - 45°C (-4°F - 113°F)
- Storage Temperature: -40°C - 70°C (-40°F - 158°F)
- Operating Humidity: 35%-80%
- Integral Driver
- Power Factor > 0.9
- THD 20%

ILLUMINATION

- G13 Medium Bi-Pin Base
- Frosted Glass Lens
- 15W
- 1900 or 2000 Lumens
- Available in 30K, 35K, 40K, 50K, and 65K
- CRI >82
- 50,000 hours @L₇₀
- Beam Angle: 210°

CODE COMPLIANCE


- cULus Listed
- RoHS Compliant
- DLC Listed
- NSF Listed



T8LED2-K T8 LED Lamp

ORDERING INFORMATION

CATALOG#	Description
T8LED2-K-15L-30K	15W, 1900 Lumens, 120-277V, 3000K
T8LED2-K-15L-35K	15W, 1900 Lumens, 120-277V, 3500K
T8LED2-K-15L-40K	15W, 1900 Lumens, 120-277V, 4000K
T8LED2-K-15L-50K	15W, 2000 Lumens, 120-277V, 5000K
T8LED2-K-15L-65K	15W, 2000 Lumens, 120-277V, 6500K



A: 42.63"
B: 47.15"
C: 1.02"