

SPECIFICATIONS

INDOOR

HOUSING

- Steel Housing
- White Finish
- On/Off Toggle Switch

ELECTRICAL

- 120V
- Hardwire Only
- Operating Temperature: -4° - 114°F (-20° - 45°C)
- Pf > .90
- 25,000 Hrs @ L₇₀

ILLUMINATION

- Frosted Acrylic Lens, non -yellowing
- 5CT: (27/30/35/40/50K)
- Beam angle: 180°

MOUNTING

- Mounting knockouts behind diffuser cover
- 3/8" Flexible conduit or 3-wire romex

CODE COMPLIANCE

- cETLus Listed for Damp Locations
- Meets UL Requirements
- Title24 JA8 Compliant
- FCC Compliant

WARRANTY

- 5 Year Warranty



UC3-EN LED Under Cabinet

ORDERING INFORMATION

CATALOG#	Length	Wattage	Lumens
UC3-EN-11L-120V-5CT	11"	6W	450 Lumens
UC3-EN-18L-120V-5CT	18"	8W	600 Lumens
UC3-EN-24L-120V-5CT	24"	12W	900 Lumens
UC3-EN-36L-120V-5CT	36"	15W	1250 Lumens
UC3-EN-42L-120V-5CT	42"	18W	1350 Lumens

