

## SPECIFICATIONS

OUTDOOR

### HOUSING

- Round cast aluminum housing with flat top
- Dark bronze finish
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

### ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F) - 55°C (131°F)
- 163,000 hours @ L<sub>70</sub>

### OPTICAL SYSTEM

- Polycarbonate lens
- MT (Selectable between 3000K - 5000K)
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- CRI: 80

### MOUNTING

- Mounts with 6" anchor bolts, order separately

### CODE COMPLIANCE

- UL Listed for Wet Locations
- IP65 Rated
- DLC Listed

### WARRANTY

- 5 Year



**VLBRL-F**  
**Round Flat**  
**LED Bollard**

| Catalog # | Low Lumens |         |         | Mid Lumens |         |         | High Lumens |         |         |
|-----------|------------|---------|---------|------------|---------|---------|-------------|---------|---------|
| VLBRL-F   | 3000K      | 4000K   | 5000K   | 3000K      | 4000K   | 5000K   | 3000K       | 4000K   | 5000K   |
|           | 1827 Lm    | 1974 lm | 1941 Lm | 2507 Lm    | 2686 Lm | 2665 Lm | 3090 Lm     | 3244 Lm | 3296 Lm |
|           | 13W        | 14W     | 13W     | 18W        | 19W     | 18W     | 23W         | 22W     | 23W     |

## ORDERING INFORMATION

### CATALOG #

VLBRL-F-1L-QT-MCT

### ACCESSORIES (Ships on Side)

VLBRL-F-ABK6 - 6" Anchor Bolts (required)

