

SPECIFICATIONS

OUTDOOR

HOUSING

- Die-cast aluminum housing painted in black
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 480V optional
- 0-10V Dimming standard
- Operating Temperature: -30°C - 50°C (-22°F - 122°F)

OPTICAL SYSTEM

- Polycarbonate lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- CR>80
- 4000K and 5000K standard

MOUNTING

- Mounting hook standard
- Yoke mounting bracket optional, provides 180° of adjustability
- 1/2" conduit can be attached to yoke mounting bracket
- Pendant Snap Hook available

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP65 Rated
- DLC Listed

WARRANTY

- 5 Year
- 10 Year Available

ORDERING INFORMATION

CATALOG #	WATTAGE	LUMENS	Driver
VLHBLED24-B-98L-QT-*	98W	14,000 Lumens	120-277V
VLHBLED24-B-150L-QT-*	150W	20,000 Lumens	120-277V
VLHBLED24-B-200L-QT-*	200W	28,000 Lumens	120-277V
VLHBLED24-B-240L-QT-*	240W	32,000 Lumens	120-277V
VLHBLED24-B-101L-480V-*	101W	14,000 Lumens	480V
VLHBLED24-B-149L-480V-*	149W	20,000 Lumens	480V
VLHBLED24-B-200L-480V-*	200W	28,000 Lumens	480V
VLHBLED24-B-238L-480V-*	238W	34,000 Lumens	480V

***Specify 40K, 50K**

OPTIONS (Factory Installed)

MODS	- Microwave Occupancy and Dimming Sensor
10YR	- 10 Year Warranty


ACCESSORIES (Ships on Side)

VLHBLED24-B-SH	- Pendant Snap Hook
VLHBLED24-B-AY-S	- Yoke Bracket - 98W/101W/149W/150W Models
VLHBLED24-B-AY-L	- Yoke Bracket - 200W/238W/240W Models
VLHBLED24-B-AR90-S	- 90° Aluminum Reflector - 98W/101W/149W/150W Models
VLHBLED24-B-AR90-L	- 90° Aluminum Reflector - 200W/238W/240W Models
VLHBLED24-B-PR90-S	- 90° Polycarbonate Reflector - 98W/101W/149W/150W Models
VLHBLED24-B-PR90-L	- 90° Polycarbonate Reflector - 200W/238W/240W Models
VLHBLED24-B-REM	- Sensor Remote Control



VLHBLED24-B LED Highbay

98W/101W/149W/150W



200W/239W/240W

