

SPECIFICATIONS

INDOOR

HOUSING

- Die-formed cold rolled steel housing
- High reflectance baked white enamel finish
- Offered in 4', and 8' models
- 2^{3/4"} H x 2^{3/8"} W

ELECTRICAL

- Quad Tap (QT) - 120-277V
- Dimmable driver standard
- PF > 0.90
- THD < 20%

OPTICAL SYSTEM

- PMMA Lens
- CRI > 80
- Offered in 35K, 40K, 50K
- 122,000 Hours @ L₇₀

MOUNTING

- Can be surface, stem, or chain mounted

CODE COMPLIANCE

- cULus Listed for Damp Locations
- DLC Listed
- FCC Compliant

WARRANTY

- 5 Year



VLST3-B LED Slim Strip

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color	Size
VLST3-B-33L-QT-35K	33W	4,278	3500K	4'
VLST3-B-62L-QT-35K	62W	8,129	3500K	8'
VLST3-B-62L-QT-40K	62W	8,131	4000K	8'
VLST3-B-62L-QT-50K	62W	8,135	5000K	8'

OPTIONS (Factory Installed)

- OCS** - Occupancy Sensor

Accessories (Field Installed, Order Separately)

- EBCP-5W** - 5W Emergency Ballast - Remote Mount
EBCP-10W - 10W Emergency Ballast - Remote Mount

ELECTRICAL INFORMATION

Catalog #	Input Amps (A)		
	120V	240V	277V
VLST3-B-4' (35K)	0.28	0.14	0.12
VLST3-B-4' (40K)	0.28	0.14	0.12
VLST3-B-8' (35K)	0.52	0.26	0.20
VLST3-B-8' (40K)	0.52	0.26	0.20
VLST3-B-8' (50K)	0.46	0.26	0.20

COMPATIBILITY

Compatible Dimmers

Manufacturer	Model #	Dimming Range	Load Switching Capacity
Leviton	IP710-LFZ	10% - 100%	1200W
Lutron	DVSTV	10% - 100%	450W
General Protech	DMD-LED3-102	10% - 100%	600W

Installed Emergency Drivers

Catalog #	EBCP-5W		EBCP-10W	
	Watts	EM Lumens	Watts	EM Lumens
VLST3-B-4'	5.0W	650	10.7W	1391
VLT3-B-8'	5.0W	650	10.7W	1391