

SPECIFICATIONS

INDOOR

FEATURES

- Built-in Electronic Driver
- 120V
- Dimmable Driver
- On/Off Rocker Switch
- CRI ≥90
- Rear panel punch-in electrical connectors for easy wiring
- Linkable up to 400W
- Offered in 2700K
- White housing
- Units include: Captive screws, plastic washers, wire connectors, end-to-end connectors, rocker switch, and 3/8" diecast connector

CODE COMPLIANCE

- cULus Listed for Damp Locations
- Title24 Compliant
- RoHS Compliant
- Energy Star Rated

WARRANTY

- 5 Year



VLUC3-B-B LED Under Cabinet Light

ORDERING INFORMATION

| CATALOG# | Length | Wattage | Lumens |
|------------------|--------|---------|-------------|
| VLUC3-B-8L-120V | 8" | 4W | 210 Lumens |
| VLUC3-B-11L-120V | 11" | 6W | 470 Lumens |
| VLUC3-B-14L-120V | 14" | 9W | 510 Lumens |
| VLUC3-B-18L-120V | 18" | 11W | 690 Lumens |
| VLUC3-B-22L-120V | 22" | 11W | 750 Lumens |
| VLUC3-B-29L-120V | 29" | 13W | 950 Lumens |
| VLUC3-B-32L-120V | 32" | 15W | 1100 Lumens |
| VLUC3-B-36L-120V | 36" | 16W | 1130 Lumens |
| VLUC3-B-48L-120V | 48" | 18W | 1430 Lumens |

OPTIONS (Factory Installed)

| | | |
|------|---|---------------------------------|
| PC | - | Power Cord |
| LC1N | - | Linkable Connector with 1" Wire |
| LC2N | - | Linkable Connector with 2" Wire |
| LC3N | - | Linkable Connector with 3" Wire |
| LC2F | - | Linkable Connector with 2' Wire |

