

SPECIFICATIONS

INDOOR

HOUSING

- Light gray polycarbonate housing
- Stainless steel clips
- Easy installation in new construction or retrofit
- Screw in sensor ready

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10vdc dimmable driver standard
- Operating Temperature: -40°C - 50°C (-40°F - 122°F)
- 2kV Surge protection
- Power factor > .90
- THD <20%

OPTICAL SYSTEM

- Polycarbonate Lens
- CRI >80
- MCT:Selectable between: 35K/40K/50K
- 174,000 @ L₇₀

MOUNTING

- Surface mounting kit standard and V-Hooks included
- Optional cable mount kit provides luminaire suspension

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP66 Rated
- IK10 Rated
- NEMA 4X
- DLC Listed
- Complies with FCC Part 15, class A

WARRANTY

- 5 Year



VLVT13-B-MCT

Wattage and Color Selectable Vapor Tight

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	CCT
VLVT13-B-8X1L-QT-MCT	66W - 95W	9280 - 13,716 Lm	35K/40K/50K

Accessories (Ships on Side)

HD09VR-PH5-1-90*	- Passive Infrared Occupancy Sensor with 90° Elbow Adapter (max height: 39')
HD09VR-MH5-1-90*	- Microwave Step-Dimming Occupancy Sensor with 90° Elbow Adapter (max height: 49')
HD05R	- Remote Control for all Sensors (required for HD07 Series)
HD07VR-A-1	- 12VDC Screw-In Photocell, RCA Jack
VLHBLED-B-GK3	- 3 Meter Cable Mount Kit
VLHBLED-B-GK5	- 5 Meter Cable Mount Kit



	L	W	H
8X1L	94.49"	3.74"	3.11"

LUMEN INFORMATION

Catalog #	Low Lumens			Mid Lumens			High Lumens		
VLVT13-B-8X1L	3500K	4000K	5000K	3500K	4000K	5000K	3500K	4000K	5000K
	9386 Lm	9596 Lm	9280 Lm	10,574 Lm	10,837 Lm	10,469	12,340	12,716	12,223 Lm
	69W	66W	69W	79W	76W	79W	92W	90W	95W

ELECTRICAL INFORMATION

Catalog #	Input Amps (A)								
	Low Lumens			Mid Lumens			High Lumens		
	120V	240V	277V	120V	240V	277V	120V	240V	277V
VLVT13-B-8X1L (35K)	0.57	0.29	0.25	0.66	0.33	0.27	0.77	0.39	0.33
VLVT13-B-8X1L (40K)	0.55	0.28	0.24	0.63	0.32	0.27	0.75	0.38	0.33
VLVT13-B-8X1L (50K)	0.58	0.25	0.25	0.66	0.33	0.29	0.79	0.40	0.34