

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Bronze powdercoat bronze finish
- Offered with Angled or Straight shade
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket
- 1/2" coin plugs with O-rings for conduit and photocell

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable driver available
- Operating Temperature -40°C - 50°C

OPTICAL SYSTEM

- Clear glass lenses available
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- Type V distribution
- 187,000 Hours @ L₇₀

ILLUMINATION

- 22W LED
- 27 System Watts

MOUNTING

- Pendant mount, or surface mount for wall or ceiling

CODE COMPLIANCE

- cSAus Listed for Wet Locations
- Meets UL Requirements
- IP66 Rated
- Wildlife Lighting Certified - Cert #2018-001
- Turtle-Safe

WARRANTY

- 5 Year
- 10 Year Available

ORDERING INFORMATION

CATALOG #	Wattage	Mount
VP4-Q-W-23L-QT-AMB-AS	23W	Wall
VP4-Q-S-23L-QT-AMB-*	23W	Surface
VP4-Q-P-23L-QT-AMB-*	23W	Pendant

*Specify **AS-Angled Shade**; **SS-Straight Shade**

Wall Mount offered with Angled Shade only

OPTIONS (Factory Installed)


SGP	-	Surge Protection
SGF	-	Single Fuse
DBF	-	Double Fuse
CC	-	Custom Color
10YR	-	10 Year Warranty

ACCESSORIES (Order Separately)


VP4-Q-WG -	Wire Guard
VP4-Q-SPR -	Swivel Pendant Mount - Round (3/4" Conduit)
VP4-Q-SPS -	Swivel Pendant Mount - Square (3/4" Conduit)



VP4-Q-AMB Amber LED Vapor Proof



	VP4-Q-S	VP4-Q-P
Diameter (C)	16"	16"
Height (A)	12"	12 3/4"
Shade (B)	5 1/2"	5 1/2"



	VP4-Q-W	VP4-Q-S	VP4-Q-P
Diameter (D)	11 3/4"	11 3/4"	11 3/4"
Height (A)	19"	15 1/2"	16 1/4"
Shade (B)	8 3/4"	8 3/4"	8 3/4"

Amber LED - Spectral Chart

