

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Bronze powdercoat bronze finish
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable Driver standard (59W model only)
- Starting Temperature: -40°C (-40°F)

OPTICAL SYSTEM

- Polycarbonate opal lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- CRI: 70+
- 5000K standard, 30K and 40K available

MOUNTING

- Cast-In template for mounting directly over a 4" recessed outlet box, or 1/2" surface conduit
- Quick mount bracket also available

CODE COMPLIANCE

- cULus Listed for Wet Location
- If being wall mounted, fixture is Damp Location only
- Meets DLC Requirements

WARRANTY

- 5 Year
- 10 Year Available



**VR20-C
LED Canopy Light**

ORDERING INFORMATION

CATALOG #	LUMENS	WATTAGE	COLOR
VR20-C-40L-QT-50K	3,843	40W	5000K
VR20-C-59L-QT-50K	5,771	59W	5000K

OPTIONS (Factory Installed)

PC1	-	120V Photocell
PC2	-	208-277V Photocell
30K	-	3000K (extended lead time)
40K	-	4000K (extended lead time)
10YR	-	10 Year Warranty
CC	-	Custom Color

ACCESSORIES (Ships on Side)

VR20-C-QM-	Quick Mount Bracket
------------	---------------------

