

SPECIFICATIONS

INDOOR

HOUSING

- Stainless steel caps and clips
- Stamped end caps
- Embossed direction indicators on end caps
- Precision molded ring gaskets
- Fixtures are linkable
- Offered in 2', 4', and 8' models

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP65/IP66/IP67/IP69
- NSF Rated
- RoHS Compliant
- BAA Compliant
- NEMA 4X

ELECTRICAL

- Quad Tap (QT) - 120-277V

WARRANTY

- 5 Year

OPTICAL SYSTEM

- Polycarbonate and Frosted lens available
- CRI >80
- Offered in 30K, 35K, 40K, and 50K

MOUNTING

- Up/Down mounting strap
- Directional rigid mounting bracket
- Directional cable mounting



VTFP1-K NSF Rated LED Vaportight

MODEL #	Size x Wattage	Voltage	CCT
VTFP1-K	2FT	QT (120-277V)	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		
	4FT		
	4X17L (17W, 3220 Lm)		
	4X24L (24W, 4480 Lm)		
	4X30L (30W, 5705 Lm)		
	4X37L (37W, 6910 Lm)		
	4X48L (48W, 8640 Lm)		
	4X70L (70W, 11,797 Lm)		
	8FT		
	8X17L (17W, 3220 Lm)		
	8X24L (24W, 4480 Lm)		
	8X30L (30W, 5705 Lm)		
	8X37L (37W, 6910 Lm)		
	8X48L (48W, 8640 Lm)		
	8X70L (70W, 11,797 Lm)		
	8X74L (74W, 13,820 Lm)		
	8X96L (96W, 17,280 Lm)		
	8X140L (140W, 23,594 Lm)		

OPTIONS (Factory Installed)

EM	- Emergency Ballast
SR	- Silver Reflector
OCS	- External Occupancy Sensor
SSL	- Stainless Steel Latch
PCL	- Polycarbonate Lens
FL	- Frosted Lens



