

SPECIFICATIONS

INDOOR

HOUSING

- Heavy gauge die-formed cold rolled steel housing in white finish
- Polyester or baked white enamel powder coat
- Available in 2', and 4' housings
- Call about 18" and 3' housing options

ELECTRICAL

- Quad Tap (QT) - 120-277V
- THD <20%
- 4kV Surge Protection
- 50,000 hours @ L₇₀

OPTICAL SYSTEM

- White acrylic lens
- CRI >80
- Power Factor >.90
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- 7/8" Knockouts in housing for surface mount
- Fixture may be ounted individuallu or may be used in a continuous run

CODE COMPLIANCE

- cULus Listed for Damp Locations
- BAA Compliant
- FCC Compliant
- RoHS Compliant

WARRANTY

- 5 Year



WMB-K LED Wall Bracket

ORDERING INFORMATION

MODEL #	Size/Wattage	Driver	CT
WMB-K	2'	QT (120-277V)	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		
	4'		
	4X17L (17W, 3220 Lm)		
	4X24L (24W, 4480 Lm)		
	4X30L (30W, 5705 Lm)		
	4X37L (37W, 6910 Lm)		
	4X48L (48W, 8640 Lm)		
	4X70L (70W, 11797 Lm)		

OPTIONS (Factory Installed)

EM5	- 5W Emergency Battery
EM10	- 10W Emergency Battery
EM14	- 14W Emergency Battery
OCSD	- Bi-Level Dimming System
CBF	- Center Baffle
FBF	- Front/Top Baffle
3WY	- 3-Way Directional Lighting (Requires CBF or FBF option)