

SPECIFICATIONS

INDOOR

HOUSING

- Die-formed cold rolled steel housing in white finish
- Available in 2', and 4' housings
- Call about 18" and 3' housing options

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V

OPTICAL SYSTEM

- White acrylic lens
- CRI >80
- Power Factor >.90
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- 7/8" Knockouts in housing for surface mount
- Fixture may be ounted individuallu or may be used in a continuous run

CODE COMPLIANCE

- cULus Listed for Damp Locations
- BAA Compliant

WARRANTY

- 5 Year

ORDERING INFORMATION

MODEL #	Size/Wattage	Driver	CT
WMB-K	2'	QT (120-277V)	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		
	4'		
	4X20L (20W, 3159 Lm)		
	4X30L (30W, 4480 Lm)		
	4X40L (40W, 6318 Lm)		
	4X42L (42W, 5684 Lm)		
	4X60L (60W, 8960 Lm)		
	4X84L (84W, 11368 Lm)		

OPTIONS (Factory Installed)

EM	- LED Emergency Ballast
OCSI	- Internal Occ Sensor
OCSE	- External Occ Sensor
DIM	- Bi-Level Dimming
3WY	- 3-Way System
GO	- Grounded Outlet
TS	- Toggle Switch
PCS	- Pull Chain Switch
NL	- Night Light
PCL	- Polycarbonate Lens (white acrylic standard)
PRL	- Prismatic Lens (white acrylic standard)
FRL	- Frosted Lens (over LED boards)
SIL	- Silver Reflector
DL	- Down Light Only



WMB-K LED Wall Bracket