

SPECIFICATIONS

INDOOR

HOUSING

- Vandal-proof housing
- Heavy-gauge die formed steel
- Polyester or baked white enamel powder coat
- Available in 2', and 4' housings
- Call about 18" and 3' housing options

ELECTRICAL

- Quad Tap (QT) - 120-3V

OPTICAL SYSTEM

- W.125 Prismatic polycarbonate lens
- CRI >80
- Power Factor >.90
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- 7/8" Knockouts in housing for surface mount
- Fixture may be mounted individually or may be used in a continuous run

CODE COMPLIANCE

- cULus Listed for Damp Locations
- BAA Compliant

WARRANTY

- 5 Year



WMB2-K LED Vandal Resistant Wall Bracket

ORDERING INFORMATION

MODEL #	Size/Wattage	Driver	CT
WMB2-K	2'	QT (120-277V)	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		
	4'		
	4X17L (17W, 3220 Lm)		
	4X24L (24W, 4480 Lm)		
	4X30L (30W, 5705 Lm)		
	4X37L (37W, 5705 Lm)		
	4X48L (48W, 8640 Lm)		
	4X70L (70W, 11,797 Lm)		

OPTIONS (Factory Installed)

- EM5** - 5W Emergency Battery
- EM10** - 10W Emergency Battery
- EM14** - 14W Emergency Battery
- OCSD** - Bi-Level Dimming System
- 3WY** - 3-Way Directional Lighting (Requires CBF or FBF option)
- CBF** - Center Baffle
- FBF** - Front/Top Baffle

