

SPECIFICATIONS

INDOOR

HOUSING

- Vandal-proof housing
- Heavy-gauge die formed steel
- Available in 2', and 4' housings
- Call about 18" and 3' housing options

ELECTRICAL

- Quad Tap (QT) - 120-3V

OPTICAL SYSTEM

- W.125 Prismatic polycarbonate lens
- CRI >80
- Power Factor >.90
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- 7/8" Knockouts in housing for surface mount
- Fixture may be mounted individually or may be used in a continuous run

CODE COMPLIANCE

- cULus Listed for Damp Locations
- BAA Compliant

WARRANTY

- 5 Year



WMB2-K LED Vandal Resistant Wall Bracket

ORDERING INFORMATION

MODEL #	Size/Wattage	Driver	CT
WMB2-K	<u>2'</u>	QT (120-277V)	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		
	<u>4'</u>		
	4X17L (17W, 3220 Lm)		
	4X24L (24W, 4480 Lm)		
	4X37L (37W, 5705 Lm)		
	4X48L (48W, 8640 Lm)		
	4X70L (70W, 11,797 Lm)		

OPTIONS (Factory Installed)

EM	- LED Emergency Ballast
OCSI	- Internal Occ Sensor
OCSE	- External Occ Sensor
DIM	- Bi-Level Dimming
3WY	- 3-Way System
GO	- Grounded Outlet
TS	- Toggle Switch
PCS	- Pull Chain Switch
NL	- Night Light
PCL	- Polycarbonate Lens (white acrylic standard)
PRL	- Prismatic Lens (white acrylic standard)
FRL	- Frosted Lens (over LED boards)
SIL	- Silver Reflector
DL	- Down Light Only

