

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Bronze powdercoat finish
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket
- Includes quick mount back plate for easy wall mounting

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)

OPTICAL SYSTEM

- UV-resistant borosilicate glass lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- MCT (30K/40K/50K)
- CRI > 70
- PF > 0.90
- THD < 20%

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Listed
- CEC Title24 Compliant
- RoHS Compliant

WARRANTY

- 5 Year



WP28-C-MCT

Wattage Selectable

LED Wall Pack

ORDERING INFORMATION

CATALOG #	Wattage	Lumens
WP28-C-1L-QT-MCT	30W / 50W / 72W	3800 / 6400 / 8600Lm

OPTIONS (Factory Installed)

EM	- 8W Emergency Battery
OCS	- Occupancy Sensor
PC	- Photocell
SGP	- 10kV Surge Protection
WT	- Wide Throw Distribution

