

SPECIFICATIONS

OUTDOOR

HOUSING

- Cast aluminum housing
- Dark bronze powdercoat finish
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)

OPTICAL SYSTEM

- High impact polycarbonate lens
- MCT (Selectable between 30K/40K/50K)
- CRI>80
- Internal switchable photocell

MOUNTING

- Quick mount backplate for easy installation

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Premium Approved
- RoHS Compliant
- FCC

WARRANTY

- 5 Year



WP3.5-C-MCT

Color and Wattage Selectable LED Wall Pack

ORDERING INFORMATION

CATALOG #	Wattage	Lumens*	CCT
WP3.5-C-1L-QT-MCT	30W / 42W / 46W	6520 Lm	30K/40K/50K
WP3.5-C-3L-QT-MCT	62W / 92W / 100W	14,075 Lm	30K/40K/50K

*Shows highest wattage at 50K

OPTIONS (Factory Installed)

OCS	- Occupancy Sensor
EM	- 8W Battery Backup
SGP1	- 10kV Surge Protection
SGP2	- 20kV Surge Protection

