

SPECIFICATIONS

OUTDOOR

HOUSING

- Die-Cast aluminum housing
- Dark bronze powdercoat finish standard
- Also available in white, black, gray, or custom finish
- Silicone rubber gasket
- Mounts on to standard recessed junction box

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable driver standard
- 6Kv Surge protection standard
- Operating Temperature: -40°C (-40°F) - 50°C (122°F)
- Built in switchable photocell
- 70,000 hours @ L₇₀

OPTICAL SYSTEM

- Clear acrylic lens
- Type III beam angle
- MCT (Selectable between 30K/40K/50K)
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- CRI>80

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Listed
- CA T24
- FCC
- RoHS Compliant

WARRANTY

- 5 Year



WP37-EN

Wattage and Color Selectable LED Wallpack

| CATALOG # | Wattage | Lumens | CCT |
|-------------------|---------------|--------------------------|---------------|
| WP37-EN-1L-QT-MCT | 48W/ 64W/ 80W | 6480 / 8640 / 10,800 Lms | 30K/ 40K/ 50K |

OPTIONS (Factory Installed)

| | |
|-------|--|
| BK | - Black Housing (bronze standard) |
| WH | - White Housing (bronze standard) |
| GY | - Gray Housing (bronze standard) |
| CC | - Custom Color (bronze standard) |
| T5 | - Type V (Type III standard) |
| T4 | - Type IV (Type III standard) |
| OCS | - Bi-Level Motion and Daylight Sensor |
| OCSBT | - Bi-Level Motion and Daylight Sensor with Bluetooth Control |
| EM | - Emergency Ballast |
| SGP | - 20kV Surge Protection (6Kv standard) |

ACCESSORIES (Ships on the Side)

| | |
|---------|-----------------|
| REM2-EN | - Sensor Remote |
|---------|-----------------|

