

SPECIFICATIONS

OUTDOOR

HOUSING

- Die-Cast aluminum housing
- Dark bronze powdercoat finish standard
- Multiple mounting options available

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F) - 50°C (122°F)
- 70,000 hours @ L₇₀
- 6kV Surge Protection standard
- THD <20%
- PF >.90

OPTICAL SYSTEM

- Tempered clear flat acrylic lens
- ColorLED COB
- Red, Blue, and Green available
- CRI>80

CODE COMPLIANCE

- cETLus Listed for Wet Locations
- IP66

WARRANTY

- 5 Year



WP53.5-QCL Wattage and Color Tunable LED Wall Pack

ORDERING INFORMATION

CATALOG #	Wattage	Driver	CCT	Mounting
WP53.5-QCL	60L (60W)	QT (120-277V)	BL (Blue)	KN (1/2" NPS knuckle)
	80L (80W)		GR (Green)	SF (Slipfitter)
			RD (Red)	SB (2-piece swivel bracket)

Options (Factory Installed)

SGF	- Single Fuse
DBF	- Double Fuse
PC	- Integral Button Photocell
SGP	- 20kV Surge Protection (6kV standard)

