

SPECIFICATIONS

OUTDOOR

HOUSING

- Cast aluminum housing
- Dark bronze powdercoat finish
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F) - 50°C (122°F)
- 70,000 hours @ L₇₀
- 10kV Surge Protection standard

OPTICAL SYSTEM

- Clear acrylic lens
- Rotatable LEDs
- MCT (Selectable between 30K/40K/50K)
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- CRI>80

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Premium Approved
- FCC
- RoHS Compliant
- CA T24 Approved

WARRANTY

- 5 Year



WP58.5-EN Adjustable LED Wall Pack

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	CCT
WP58.5-EN-1L-QT-MCT	40W/60W/80W	4890 - 10,875 Lm	30K/40K/50K
WP58.5-EN-60L-QT-MCT	60W	8280 Lm	30K/40K/50K
WP58.5-EN-80L-QT-*	80W	10,875 Lm	30K or 40K or 50K

*Specify 30K, 40K, 50K

Options (Factory Installed)

EM	- 20W Integral Emergency Battery Backup
480V	- 277-480V Driver
PC	- Button Photocell for 1/2" Knockout
OCS	- Bi-Level Occupancy Sensor with Daylight Harvesting, Internal, 1/2" Knockout, includes auxiliary
OCS2	- Bi-Level Occupancy Sensor with Daylight Harvesting, External (requires remote)
OCSBT	- Bi-Level Occupancy Sensor with Daylight Harvesting, Bluetooth (requires remote), external
SGP	- 20kV Surge Protection (10kV standard)
BK	- Black Finish
WH	- White Finish
GY	- Gray Finish

Accessories (order separately, ships on side)

REM1-EN	- Remote for OCS
REM2-EN	- Remote for OCS2, OCSBT
WP58.5-EN-GS	- Shield

