

SPECIFICATIONS

MULTIFAMILY

HOUSING

- Aluminum housing available in white or black
- Enclosed and gasketed
- Can be wall or ceiling mounted

ELECTRONIC

- 120V
- Quad-Tap (120-277V)
- Dimmable Driver on 120V models

ILLUMINATION

- White polycarbonate diffuser
- 80CRI

CODE COMPLIANCE

- cETLus Listed for Wet Location
- IP65 Rated
- RoHS Compliant
- Energy Star Rated

WARRANTY

- 5 Year Warranty



WP72-G
LED Surface Light

Ordering Information

| CATALOG# | Wattage | Lumens | Color |
|-------------------------|---------|-------------|-------|
| WP72-*-G-14L-120V-30K-# | 14W | 1430 Lumens | 3000K |
| WP72-*-G-14L-120V-40K-# | 14W | 1500 Lumens | 4000K |
| WP72-*-G-22L-120V-30K-# | 22W | 1950 Lumens | 3000K |
| WP72-*-G-22L-120V-40K-# | 22W | 2130 Lumens | 4000K |
| WP72-*-G-22L-QT-30K-# | 22W | 1704 Lumens | 3000K |
| WP72-*-G-22L-QT-40K-# | 22W | 1824 Lumens | 4000K |
| WP72-*-G-32L-120V-30K-# | 32W | 2700 Lumens | 3000K |
| WP72-*-G-32L-120V-40K-# | 32W | 2750 Lumens | 4000K |

*Specify Model: **HC**-Half Cutoff; **O**-Open Face

#Specify Housing: **WH**-White; **BL**-Black

Options

- OCS - Occupancy Sensor
- EBLD - Emergency Backup (120V models only)

