VersaLED Lighting
Versatile Lighting Solutions

Project

Type

Catalog Number

SPECIFICATIONS — OUTDOOR

HOUSING
- Powder-coat, heavy duty die cast aluminum housing
- Offered in bronze, black, and white finish
- Corrosion resistant housing and hardware
- Five 1/2" knockouts: 1 on each side for easy installation

ELECTRICAL
- Quad Tap (QT) - 120-277V
- 277V - 480V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C - 50°C (-40°F - 122°F)
- 6KV Surge protection standard
- PF > 0.90

OPTICAL SYSTEM
- Clear acrylic lens
- CRI ≥ 80
- THD < 20%
- 50/60Hz
- Beam angle Type IV S
- Color Selectable (30K/40K/50K)
- PC Included
- 70,000 Hours @ L_{70}

CODE COMPLIANCE
- cULus Listed for Wet Locations
- ROHS Compliant
- Approved for CA T24
- DLC Premium Listed
- FCC CFR 47, GCC Part 15, Subpart B: 2017

WARRANTY
- 5 Year







WP75-EN
Wall Pack

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	CCT
WP75-EN-1L-QT-MCT	20W/30W/40W/50W/60W	2900 / 4350 / 7250 / 8700 Lms	30K/ 40K/ 50K
WP75-EN-2L-QT-MCT	80W/90W/100W/110W/120W	11,600/13,050/14,500/15,950/17,400Lms	30K/ 40K/ 50K

OPTIONS (Factory Installed)

EM	-	Emergency Battery Backup, Back Box
EMCW	-	Emergency Battery Back, Cold Weather
SGP	-	20kV Surge Protector
OCS	-	Bi-Level Motion and Daylight Sensor
OCSSL	-	Bi-Level Motion and Daylight Sensor with Bluetooth Control
BK	-	Black Housing (bronze standard)
WH	-	White Housing (bronze standard)
GY	-	Gray Housing (bronze standard)
480V	-	277-480V Driver

ACCESSORIES (ships on side)

REM2-EN	-	Sensor Remote



1L



2L